



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-11 CH'D DEPTH WAS 3-1/2 IS 4-3/4, WAS 4-3/4 IS 5-9/16. -13 CH'D PLACARD LOCATION CUTOUT WAS HITTING TOOL WITH LID CLOSED.	10/2/2012	RJC	SE
2	15-0145	-11 ADDED MISSING DIM 8X R.13. -13 CH'D DIM WAS .07 IS .13. -15 REPLCED CONTENTS LIST WITH RBW6505G00231-3T, DELETED LINES FROM TOOL LAYOUT, ADDED ITEM NUMBERS TO TOOL LAYOUT. ADDED -19 AND -21.	6/23/2015	RJC	JAG
3	16-0254	-11, -13, -15 CH'D DWG. TO SHEET METAL TOLERANCE. -11, -13 CH'D MATERIAL AND VENDOR WAS Y20 BLACK I.R. SPECIALTY FOAM IS ETHAFOAM 220, BLACK (CASE SOLUTIONS). -11 CH'D DIM WAS 17.00 IS 17.15, WAS 22.00 IS 22.15, WAS 6.00 IS 6.08, WAS 4X 4° IS 4X 2°, ADDED DIM 4X .65, 4X 45°. -13 CH'D DIM WAS 17.00 IS 16.96, WAS 22.00 IS 21.95, WAS 1.88 IS 1.83, WAS 4X 4° IS 4X 2°, ADDED DIM 4X .56, 4X 45°. -15 DELETED ALL TEXT HT. NOTES, CH'D NOTE WAS USE PDF FOR MANUFACTURING IS USE PDF. -19, -21 DELETED FROM BOM. DELETED -17 P/N FOR DART PLACARD.	12/5/2016	RJC	JAG



TOOL & KIT No. REFERENCE




DART KIT No.	DART TOOL No.	ORIGINAL No.
RBW6505G00231-3T	=	= 3T6505G00231
RBW6505G00231-3T-1	= RBW6522G00231-W142S-3T	= 3T6522G00231-W142S
RBW6505G00231-3T-3	= RBW6522G00231-W142AK-3T	= 3T6522G00231-W142AK
RBW6505G00231-3T-5	= RBW6522G00231-W142AJ-3T	= 3T6522G00231-W142AJ
RBW6505G00231-3T-7	= RBW6500X01611-W142H-3T	= 3T6500X01611-W142H

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	TGB/MAST OUTPUT OIL SEAL ASSEMBLY SUPPORT TOOL		RBW6522A00231-W142S-3T	1
				1	OUTPUT OIL SEAL PRESS TOOL		RBW6522A00231-W142AK-3T	1
				1	TGB/SERVO ACTUATOR OIL SEAL FIT/EXTRACTION TOOL		RBW6522A00231-W142AJ-3T	1
				1	TGB OUTPUT OIL SEAL REMOVAL AND PRESS TOOL		RBW6500X01611-W142H-3T	1
		B/O	-9	1	CASE	BLACK PLASTIC	PELICAN #APP-IM2700-E	N/S
		B/O	-11	1	BOTTOM TOOL CUSHION	ETHAFOAM 220, BLACK	6.08 X 17.15 X 22.15 (CASE SOLUTIONS)	2
		B/O	-13	1	TOP TOOL CUSHION	ETHAFOAM 220, BLACK	1.83 X 16.96 X 21.95 (CASE SOLUTIONS)	3
			-15	1	INSIDE PLACARD	PLASTIC		4
		B/O		1	DART PLACARD	ALUMINUM	#RB41011	N/S

DART AEROSPACE																							
TITLE TGB SEAL REPLACEMENT TOOL KIT																							
DWG NO. RBW6505G00231-3T	REV 3																						
<table border="1"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td></td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125/</td> </tr> <tr> <td>SPEC</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td></td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td></td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td></td> <td>AFTER PLATING</td> </tr> <tr> <td></td> <td>3. INTERPRET DIM AND TOL PER</td> </tr> <tr> <td></td> <td>ASME Y14.5M-2009</td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX ± .005 FRACTIONS ± 1/8		.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125/	SPEC	1. BREAK ALL SHARP EDGES		.015 x 45° OR .015R		2. DIMENSIONAL LIMITS APPLY		AFTER PLATING		3. INTERPRET DIM AND TOL PER		ASME Y14.5M-2009
MAT'L	UNLESS OTHERWISE SPECIFIED																						
TREAT	DIMENSIONS ARE IN INCHES																						
FINISH	.XXX ± .005 FRACTIONS ± 1/8																						
	.XX ± .01 ANGLES ± 5°																						
	.X ± .1 SURFACES = 125/																						
SPEC	1. BREAK ALL SHARP EDGES																						
	.015 x 45° OR .015R																						
	2. DIMENSIONAL LIMITS APPLY																						
	AFTER PLATING																						
	3. INTERPRET DIM AND TOL PER																						
	ASME Y14.5M-2009																						
<table border="1"> <tr> <td>DRAWN BY:</td> <td>PERRITT</td> </tr> <tr> <td>CHECKED:</td> <td>DUERFELDT</td> </tr> <tr> <td>OPPS APPR:</td> <td>ANDERSON</td> </tr> <tr> <td>QA APPR:</td> <td>LINDSAY</td> </tr> <tr> <td>APPROVED:</td> <td>GILBERT</td> </tr> </table>		DRAWN BY:	PERRITT	CHECKED:	DUERFELDT	OPPS APPR:	ANDERSON	QA APPR:	LINDSAY	APPROVED:	GILBERT												
DRAWN BY:	PERRITT																						
CHECKED:	DUERFELDT																						
OPPS APPR:	ANDERSON																						
QA APPR:	LINDSAY																						
APPROVED:	GILBERT																						
SCALE 1:8	DATE 1/3/2009																						
SHEET 1 OF 4																							

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-11 CH'D DEPTH WAS 3-1/2 IS 4-3/4, WAS 4-3/4 IS 5-9/16.	10/2/2012	RJC	SE
2	15-0145	-11 ADDED MISSING DIM 8X R.13.	6/23/2015	RJC	JAG
3	16-0254	-11 CH'D DIM WAS 17.00 IS 17.15, WAS 22.00 IS 22.15, WAS 6.00 IS 6.08, WAS 4X 4° IS 4X 2°, ADDED DIM 4X .65, 4X 45°, CH'D MATERIAL AND VENDOR WAS Y20 BLACK I.R. SPECIALTY FOAM IS ETHAFOAM 220, BLACK (CASE SOLUTIONS). CH'D DWG TO SHEET METAL TOLERANCE.	12/5/2016	RJC	JAG





BOTTOM TOOL CUSHION

DART AEROSPACE	
TITLE TGB SEAL REPLACEMENT TOOL	
DWG NO. RBW6505G00231-3T-11	REV 3
MAT'L ETHAFOAM 220, BLACK	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
.XXX ± .010 FRACTIONS ± 1/8	
.XX ± .03 ANGLES ± 1°	
.X ± .1 SURFACES = 125/✓	
SPEC	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: PERRITT	USED ON MODEL
CHECKED: DUERFELDT	AW139
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:6	DATE 1/3/2009
SHEET 2 OF 4	


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-13 CH'D PLACARD LOCATION CUTOUT WAS HITTING TOOL WITH LID CLOSED.	10/2/2012	RJC	SE
2	15-0145	-13 CH'D DIM WAS .07 IS .13.	6/23/2015	RJC	JAG
3	16-0254	-13 CH'D DIM WAS 17.00 IS 16.96, WAS 22.00 IS 21.95, WAS 1.88 IS 1.83, WAS 4X 4° IS 4X 2°, ADDED DIM 4X .56, 4X 45°. CH'D MATERIAL AND VENDOR WAS Y20 BLACK I.R. SPECIALTY FOAM IS ETHAFOAM 220, BLACK (CASE SOLUTIONS). CH'D DWG TO SHEET METAL TOLERANCE.	12/5/2016	RJC	JAG



(-13)


TOP TOOL CUSHION



DART AEROSPACE	
TITLE TGB SEAL REPLACEMENT TOOL	
DWG NO. RBW6505G00231-3T-13	REV 3
MAT'L ETHAFOAM 220, BLACK	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
.XXX ± .010 FRACTIONS ± 1/8	
.XX ± .03 ANGLES ± 1°	
.X ± .1 SURFACES = 125°	
SPEC	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: PERRITT	USED ON MODEL
CHECKED: DUERFELDT	AW139
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:6	DATE 1/3/2009
SHEET 3 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0145	-15 REPLCED CONTENTS LIST WITH RBW6505G00231-3T, DELETED LINES FROM TOOL LAYOUT, ADDED ITEM NUMBERS TO TOOL LAYOUT.	6/23/2015	RJC	JAG
3	16-0254	-15 DELETED ALL TEXT HT. NOTES, CH'D NOTE WAS USE PDF FOR MANUFACTURING IS USE PDF, CH'D DWG. TO SHEET METAL TOLERANCE.	12/5/2016	RJC	JAG



NOTE:
USE PDF.

(-15)
INSIDE PLACARD

DART AEROSPACE	
TITLE TGB SEAL REPLACEMENT TOOL KIT	
DWG NO. RBW6505G00231-3T-15	REV 3
MAT'L PLASTIC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
FEAT TREAT FINISH	.XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: PERRITT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: DUERFELDT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	AW139
APPROVED: GILBERT	
SCALE 1:2	DATE 1/3/2009
SHEET 4 OF 4	